

CGP5C332KHYDCA7317

CGP DISC Comm HV, Ceramic, 3,300 pF, 10%, 3,000 VDC, Y5P, 5 mm





The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

General Information	
Series	CGP DISC Comm HV
Style	Radial Disc
RoHS	Yes
Termination	Tin
Lead	Crimped Out
Failure Rate	N/A
AEC-Q200	No
Halogen Free	Yes

3,300 pF

3000 VDC

10%

Click here for the 3D model.

Dimensions	
D	15.5mm MAX
т	6.5mm MAX
S	5mm NOM
LL	16mm +2/-0mm
F	0.6mm +/-0.1mm
V	2.1mm +/-0.5mm

	-	
+2/-0mm	Temperature Range	-30/+85°C
1 +/-0.1mm	Temp. Coefficient	Y5P
+/-0.5mm		

Specifications Capacitance

Tolerance

Voltage DC

Packaging Specifications	
Packaging	Ammo
Packaging Quantity	750

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.