

CGP7C160JDSDCAWL25

CGP DISC Comm HV, Ceramic, 16 pF, 5%, 1,000 VDC, SL, 7.5 mm



Packaging Specifications

Packaging Quantity

Packaging



The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

| General Information | |
|---------------------|------------------|
| Series | CGP DISC Comm HV |
| Style | Radial Disc |
| RoHS | Yes |
| Termination | Tin |
| Lead | Crimped Out |
| Failure Rate | N/A |
| AEC-Q200 | No |
| Halogen Free | Yes |

16 pF

1000 VDC

5%

Click here for the 3D model.

| Dimensions | |
|------------|----------------|
| D | 5.5mm MAX |
| т | 4mm MAX |
| S | 7.5mm NOM |
| LL | 25mm MIN |
| F | 0.6mm +/-0.1mm |
| V | 1.5mm +/-0.5mm |

Bulk 200

| 25mm MIN | Temperature Range | -25/+85°C |
|----------------|-------------------|-----------|
| 0.6mm +/-0.1mm | Temp. Coefficient | SL |
| 1.5mm +/-0.5mm | | |
| | | |
| | | |

Specifications Capacitance

Tolerance

Voltage DC

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.