

## CGP7C331JGSDAA7317

Specifications Capacitance

Tolerance

Voltage DC

**Temperature Range** 

Temp. Coefficient

CGP DISC Comm HV, Ceramic, 330 pF, 5%, 2,000 VDC, SL, 7.5 mm





The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

| General Information |                  |
|---------------------|------------------|
| Series              | CGP DISC Comm HV |
| Style               | Radial Disc      |
| RoHS                | Yes              |
| Termination         | Tin              |
| Lead                | Wire Leads       |
| Failure Rate        | N/A              |
| AEC-Q200            | No               |
| Halogen Free        | Yes              |

330 pF

2000 VDC

-25/+85°C

5%

SL

Click here for the 3D model.

| Dimensions |                |
|------------|----------------|
| D          | 12mm MAX       |
| т          | 5mm MAX        |
| S          | 7.5mm NOM      |
| LL         | 16mm +2/-0mm   |
| F          | 0.6mm +/-0.1mm |
| V          | 1.7mm +/-0.5mm |

| Packaging Specifications |      |  |
|--------------------------|------|--|
| Packaging                | Ammo |  |
| Packaging Quantity       | 1500 |  |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.