## CGP7C390KGSDCAWL25

CGP DISC Comm HV, Ceramic, 39 pF, 10%, 2,000 VDC, SL, 7.5 mm





General Information	
Series	CGP DISC Comm HV
Style	Radial Disc
RoHS	Yes
Termination	Tin
Lead	Crimped Out
Failure Rate	N/A
AEC-Q200	No
Halogen Free	Yes

Dimensions	
D	6mm MAX
т	Emm MAV

T 5mm MAX
S 7.5mm NOM
LL 25mm MIN

F	0.6mm +/-0.1mm	
V	1.7mm +/-0.5mm	
Packaging Specifications		
Packaging	Bulk	

**Packaging Quantity** 

200

Specifications	
Capacitance	39 pF
Tolerance	10%
Voltage DC	2000 VDC
Temperature Range	-25/+85°C
Temp Coefficient	SI

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 05/15/2025 © 2006 - 2025 YAGEO