

CKC21X622MEGACTU

Aliases (CKC21X622MEGAC7800) KC-LINK Comm COG, Ceramic, 6,200 pF, 20%, 1,200 VDC, COG, SMD, MLCC, FT-CAP, Ultra-Stable, 2220



Click here for the 3D model.

General Information			
Series	KC-LINK Comm COG		
Style	SMD Chip		
Description	SMD, MLCC, FT-CAP, Ultra- Stable		
Features	FT-CAP, Ultra-Stable		
RoHS	Yes		
Termination	Flexible Termination		
Marking	No		
AEC-Q200	No		
Typical Component Weight	320 mg		
Shelf Life	78 Weeks		
MSL	1		

0.1% 1 kHz 1.0Vrms

100 GOhms

0% Loss/Decade Hour

	Specifications	
2220	Capacitance	6,200 pF
5.9mm +/-0.75mm	Measurement Condition	1 kHz 1.0Vrms
5mm +/-0.4mm	Tolerance	20%
2.5mm +/-0.20mm	Voltage DC	1200 VDC
0.7mm +/-0.35mm	Dielectric Withstanding Voltage	1,440 VDC
	Temperature Range	-55/+150°C
	Temp. Coefficient	COG
T&R, 180mm, Plastic Tape	Capacitance Change with 30 ppr Reference to +25°C and 0 VDC Applied (TCC)	30 ppm/C, 1kHz 1.0Vrms
500		

Dissipation Factor

Insulation Resistance

Aging Rate

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Dimensions Chip Size

Packaging

Packaging Specifications

Packaging Quantity

L W

т в




CKC21X622MEGACTU Aliases (CKC21X622MEGAC7800) KC-LINK Comm COG, Ceramic, 6,200 pF, 20%, 1,200 VDC, COG, SMD, MLCC, FT-CAP, Ultra-Stable, 2220

Capacitance and Inductance


Simulations

For the complete simulation environment please visit K-SIM.



-60.0

-80.0



Frequency (Hz)

-50.0

S21 Phase
S21 Magnitude

100.0 1.0 k 10.0 k 100.0 k 1.0 M 10.0 M 100.0 M 1.0 G 10.0 G Frequency (Hz)



CKC21X622MEGACTU

Aliases (CKC21X622MEGAC7800) KC-LINK Comm COG, Ceramic, 6,200 pF, 20%, 1,200 VDC, COG, SMD, MLCC, FT-CAP, Ultra-Stable, 2220

These are simulations.

This is not a specification!

The responses shown represent the typical response for each part type. Specific responses may vary, depending on manufacturing variation affects of all parameters involved, including the specified tolerances applied to capacitance and unspecified variations of ESR, ESL, and leakage resistance.

The responses shown do not represent a specified or implied maximum capability of the device for all applications.

- The ESR used for ripple "Ripple Current/Voltage vs. Frequency" plots is the ESR at ambient temperature.

- The ESR used for hipple klipple current/ voltage vs. requericy plots is the ESR at an originatine.
 The ESR in the "Temperature Rise vs. Ripple Current" plots is adjusted to each incremental temperature rise before the power and ripple current is calculated.
 The effects shown herein are based on measured data from a multiple part sample of the parts in question.
 Ripple capability of this device will be factored by thermal resistance (Rth) created by circuit traces (addi affects of all parameters involved, including the specified tolerances applied to capacitance and unspecified variations of ESR, ESL, and leakage resistance.
 The peak voltages generated in the "Temperature Rise vs. Combined Ripple Currents" plot are calculated for each frequency and are not combined with voltages are applied to reach previous the burger of the parts.
- generated at any other harmonics.
 Please consult with the catalog or field applications engineer for maximum capability of the device in specific applications.

All product information and data (collectively, the "Information") are subject to change without notice.

KEMET K-SIM is designed to simulate behavior of components with respect to frequency, ambient temperature, and DC bias levels. The responses shown represent the typical response for each part type. Specific responses may vary, depending on manufacturing variation effects of all parameters involved, including the specified tolerances applied to capacitance and unspecified variations of ESR, ESL, and leakage resistance.

All Information given herein is believed to be accurate and reliable, but is presented without guarantee, warranty, or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

If you have any questions please contact K-SIM.