## EDT227M025S9PAA

**General Information** 


**Specifications** 

Capacitance Tolerance

Voltage DC







Series	EDT Aluminum Electrolytic	
Dielectric		
Style	SMD Can	
Description	Surface Mount, Aluminum Electrolytic	
RoHS	Yes	
Lead	V-Chip	
Qualifications	AEC-Q200	
AEC-Q200	Yes	

220 uF

25 VDC, 32 VDC (Surge)

20%

Click here for the 3D model.

Dimensions	
D	10mm +/-0.5mm
L	10.2mm +/-0.3mm
W	0.9mm +/-0.2mm
F	0.3mm MAX
A	10.3mm +/-0.2mm
В	10.3mm +/-0.2mm
С	13mm MAX
E	3.2mm +/-0.2mm
G	0.7mm +/-0.2mm
P	4.6mm +/-0.2mm
- 1 · 0 · 10 · 11	

T&R

Packaging

F	0.3mm MAX	Temperature Range	-40/+125°C
A	10.3mm +/-0.2mm	Rated Temperature	125°C
В	10.3mm +/-0.2mm	Life	2000 Hrs
С	13mm MAX	Dissipation Factor	18%
E	3.2mm +/-0.2mm	Ripple Current	180 mAmps (120Hz 125C)
G	0.7mm +/-0.2mm	High Temperature Solder	Yes
P	4.6mm +/-0.2mm	Leakage Current	55 uA (2min 20°C)
		Impedance Ratio at -25C	2
Packaging Specifications		Impedance Ratio at -40C	3

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 11/18/2025 © 2006 - 2025 YAGEO