
## EDT337M025A9PAA







General Information	
Series	EDT
Dielectric	Aluminum Electrolytic
Style	SMD Can
Description	Surface Mount, Aluminum Electrolytic
RoHS	Yes
Lead	V-Chip
AEC-Q200	No

330 uF

25 VDC, 32 VDC (Surge)

20%

Click here for the 3D model.

Dimensions		
D	10mm +/-0.5mm	
L	10.2mm +/-0.3mm	
W	0.9mm +/-0.2mm	
F	0.3mm MAX	
A	10.3mm +/-0.2mm	
В	10.3mm +/-0.2mm	
С	13mm MAX	
E	3.2mm +/-0.2mm	
G	0.7mm +/-0.2mm	
Р	4.6mm +/-0.2mm	
Packaging Specifications		

T&R

Packaging

F	0.3mm MAX	Temperature Range	-40/+125°C
A	10.3mm +/-0.2mm	Rated Temperature	125°C
В	10.3mm +/-0.2mm	Life	2000 Hrs
С	13mm MAX	Dissipation Factor	18%
E	3.2mm +/-0.2mm	Ripple Current	180 mAmps (120Hz 125C)
G	0.7mm +/-0.2mm	High Temperature Solder	Yes
Р	4.6mm +/-0.2mm	Leakage Current	82.5 uA (2min 20°C)
		Impedance Ratio at -25C	2
Packaging Specifications		Impedance Ratio at -40C	3

**Specifications** Capacitance

Tolerance

Voltage DC

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 11/02/2025 © 2006 - 2025 YAGEO