



The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

Click [here](#) for the 3D model.

#### General Information

|                |                           |
|----------------|---------------------------|
| Series         | ERK610 SFTY X1-440 Y2-300 |
| Style          | Radial Disc               |
| RoHS           | Yes                       |
| Termination    | Tin                       |
| Lead           | Wire Leads                |
| Qualifications | UL, CSA, CAN, ENEC, VDE   |
| AEC-Q200       | No                        |

#### Specifications

|                       |                            |
|-----------------------|----------------------------|
| Capacitance           | 150 pF                     |
| Tolerance             | 20%                        |
| Voltage AC            | 440 VAC (X1), 300 VAC (Y2) |
| Temperature Range     | -40/+125°C                 |
| Temp. Coefficient     | Y5T                        |
| Dissipation Factor    | 2.5%                       |
| Insulation Resistance | 6 GOhms                    |
| Safety Class          | X1/Y2                      |

#### Dimensions

|   |                 |
|---|-----------------|
| D | 8mm MAX         |
| T | 6mm MAX         |
| S | 10mm +/-0.8mm   |
| F | 0.6mm +/-0.05mm |
| V | 1.9mm +/-0.5mm  |

#### Packaging Specifications

|           |   |
|-----------|---|
| Packaging | T&R, H = 18mm, Component Pitch = 25.4mm |
|-----------|---|