





ESH, Aluminum, Aluminum Electrolytic, 22 uF, 20%, 250 VDC, -25/+105°C,



TERMINAL END VIEW



Click here for the 3D model.

General Information	
Series	ESH
Dielectric	Aluminum Electrolytic
Description	High CV Single Ended Aluminum Electrolytic
RoHS	Yes
Lead	Wire Leads
AEC-Q200	No

Dimensions		
D	10mm +/-0.5mm	
L	20mm +2.0/-0mm	
S	5mm +/-0.5mm	
LL Negative	15mm MIN	
LL Positive	20mm MIN	
НО	18.5mm +/-0.75mm	
F	0.6mm NOM	
Packaging Specifications		

r	O.OITIIITINOIM	
Packaging Specifications		
Packaging	Ammo	

Specifications	
Capacitance	22 uF
Tolerance	20%
Voltage DC	250 VDC, 300 VDC (Surge)
Temperature Range	-25/+105°C
Rated Temperature	105°C
Life	2000 Hrs
Dissipation Factor	15% 120Hz 25C
Ripple Current	140 mAmps (120Hz 105C)
Leakage Current	175 uA (2min 20°C)
Impedance Ratio at -25C	4

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 10/29/2025 © 2006 - 2025 YAGEO