





ESY, Aluminum, Aluminum Electrolytic, 220 uF, 20%, 50 VDC, -40/+105°C, 5 mm



TERMINAL END VIEW



Click here for the 3D model.

| General Information |  |
|---------------------|--|
| Series              | ESY  |
| Dielectric          | Aluminum Electrolytic                      |
| Description         | LowZ Single Ended Aluminum<br>Electrolytic |
| Features            | Low Z                                      |
| RoHS                | Yes  |
| Lead                | Wire Leads                                 |
| AEC-Q200            | No   |

| Dimensions  |               |
|-------------|---------------|
| D           | 10mm +/-0.5mm |
| L           | 15mm +2mm     |
| S           | 5mm +/-0.5mm  |
| LL Negative | 15mm MIN      |
| LL Positive | 20mm MIN      |
| F           | 0.6mm NOM     |
|             |               |

| Packaging Specifications |           |
|--------------------------|-----------|
| Packaging                | Bulk, Bag |

| Specifications          |                          |
|-------------------------|--------------------------|
| Capacitance             | 220 uF                   |
| Tolerance               | 20%                      |
| Voltage DC              | 50 VDC, 63 VDC (Surge)   |
| Temperature Range       | -40/+105°C               |
| Rated Temperature       | 105°C                    |
| Life                    | 4000 Hrs                 |
| Dissipation Factor      | 10% 120Hz 20C            |
| ESR                     | 0.042 Ohms (100kHz 20C)  |
| Ripple Current          | 1370 mAmps (100kHz 105C) |
| Leakage Current         | 110 uA (2min 20°C)       |
| Impedance Ratio at -25C | 2                        |
| Impedance Ratio at -40C | 3                        |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 11/05/2025 © 2006 - 2025 YAGEO