

## F461DU335J250R

Not for New Design

F461, Film, Metallized Polypropylene, General Purpose, 3.3 uF, 5%, 250 VDC, 85°C, 22.5 mm



Click [here](#) for the 3D model.

### General Information

|                          |   |
|--------------------------|---|
| Series                   | F461  |
| Dielectric               | Metallized Polypropylene  |
| Style                    | Radial  |
| Features                 | MKP, Pulse  |
| RoHS                     | Yes   |
| Termination              | Tinned Wire   |
| Lead                     | Wire Leads  |
| AEC-Q200                 | No  |
| Typical Component Weight | 9.078 g   |
| Miscellaneous            | The Rated Voltage Decreases 2%/C Between +85C And +105C (1.25%/C For AC). ClimCat: 55/105/56. |
| Notes                    | Series Replaced by R75.   |

### Specifications

|                       |                         |
|-----------------------|-------------------------|
| Capacitance           | 3.3 uF                  |
| Tolerance             | 5%                      |
| Voltage DC            | 250 VDC, 150 VDC (105C) |
| Voltage AC            | 160 VAC                 |
| Temperature Range     | -55/ +105°C             |
| Rated Temperature     | 85°C                    |
| Dissipation Factor    | 0.1% 1kHz               |
| Insulation Resistance | 9.091 GOhms             |
| Max dV/dt             | 125 V/us                |
| Inductance            | 6 nH                    |

### Dimensions

|    |                    |
|----|--------------------|
| L  | 26mm -0.5mm        |
| H  | 22mm -0.5mm        |
| T  | 13mm -0.5mm        |
| S  | 22.5mm +0.6/-0.1mm |
| H0 | 18.5mm +/-0.5mm    |
| F  | 0.8mm +/-0.05mm    |
| G  | 0.5mm NOM          |

### Packaging Specifications

|                    |                         |
|--------------------|-------------------------|
| Packaging          | Ammo, 360x340x59mm, Box |
| Packaging Quantity | 200                     |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.