


FMU0H334ZF

Aliases (USCFMU0H334Z00) FMU, Supercapacitors, Radial Molded, 0.33 F, -20/+80%, 5.5 VDC, Wire Leads, 5 mm



General Information	
Series	FMU
Style	Radial Molded
Description	Radial Molded Double Layer Capacitor
RoHS	Yes
Lead	Wire Leads
Qualifications	AEC-Q200
AEC-Q200	Yes
Typical Component Weight	3.8 g
Miscellaneous	DischargeValue = 0.33 F.

Specifications Capacitance 0.33 F -20/+80% Tolerance Voltage DC 5.5 VDC -40/+105°C **Temperature Range Rated Temperature** 105°C ESR 25 Ohms (1kHz) Current (at 30 minutes after 0.5 mAmps charging)

Click here for the 3D model.

14mm +/-0.5mm
15mm +/-0.5mm
9mm +/-0.5mm
5mm +/-0.5mm
5mm +/-1mm
0.4mm +/-0.1mm
0.6mm +/-0.1mm
0.6mm +/-0.1mm

Packaging Specifications

Packaging	Bulk, Bag
Packaging Quantity	400

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.