


HT14BN392JN

Aliases (HT14BN392J)

Obsolete

HP LDD Indust COG HT200C, Ceramic, 3,900 pF, 5%, 50 VDC, COG



General Information	
Series	HP LDD Indust COG HT200C
RoHS	No
Prop 65	WARNING: Cancer and reproductive harm - https://www.p65warnings.ca.gov /
Termination	Nickel
Lead	Wire Leads
Failure Rate	N/A
AEC-Q200	No
Notes	Lead Length Shown Is For Parts Supplied In Bulk, See Packaging Specifications For Lead Lengths When Not Provided In Bulk.

Dimensions	
D	3.94mm MAX
L	10.16mm MAX
LL	3.175mm MIN
F	0.635mm +0.102/-0.051mm

_	10.1011111111177	Tolerance	370
LL	3.175mm MIN	Voltage DC	50 VDC
F	0.635mm +0.102/-0.051mm	Dielectric Withstanding Voltage	125 VDC
		Temperature Range	-55/+200°C
Packaging Specifications		Temp. Coefficient	COG
Packaging	Waffle, Tray	Dissipation Factor	0.15%
Packaging Quantity 1		Inculation Desistance	100 COhma

Specifications	
Capacitance	3,900 pF
Tolerance	5%
Voltage DC	50 VDC
Dielectric Withstanding Voltage	125 VDC
Temperature Range	-55/+200°C
Temp. Coefficient	COG
Dissipation Factor	0.15%
Insulation Resistance	100 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 12/21/2025 © 2006 - 2025 YAGEO