




Obsolete KEMET, L-RMQ, Ferrite, +/-0.3 nH, 5,600 pH



| General Information |                 |
|---------------------|-----------------|
| Series              | L-RMQ           |
| Style               | SMD Multi-Layer |
| Core                | Ferrite         |
| RoHS                | Yes             |

| Dimensions |                 |
|------------|-----------------|
| L          | 1mm +/-0.05mm   |
| W          | 0.5mm +/-0.05mm |
| Т          | 0.5mm +/-0.05mm |
|            |                 |

| Packaging Specifications |       |
|--------------------------|-------|
| Packaging                | T&R   |
| Packaging Quantity       | 10000 |

| Specifications          |   |
|-------------------------|---|
| Inductance              | 0.0056 uH (100 MHz)                       |
| Inductance Tolerance    | +/-0.3 nH                                 |
| Inductance              | 5,600 pH                                  |
| Rated Current           | 420 mAmps (MAX), 550 mAmps (Self Heating) |
| DC Resistance           | 200 mOhms                                 |
| DC Resistance           | 0.2 Ohms                                  |
| Quality Factor          | 48 at 800 MHz, 65 at 1500 MHz             |
| Self-Resonant Frequency | 4000 MHz MIN                              |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 11/17/2025 © 2006 - 2025 YAGEO