



Click [here](#) for the 3D model.

#### General Information

|             |                                                         |
|-------------|---------------------------------------------------------|
| Series      | KPS-MCL Indust COG HT200C                               |
| Style       | Leaded Stacked Chip                                     |
| Description | Low Loss, Low ESR, Stacked Ceramic Chips                |
| Features    | 200C, Low ESR, High Thermal Stability, Bulk Capacitance |
| RoHS        | With Exemptions                                         |
| REACH       | SVHC (Pb - CAS 7439-92-1)                               |
| SCIP Number | 297427bb-2a48-4853-b594-641304a2cc24                    |
| Termination | Silver                                                  |
| Lead        | Straight Leads                                          |
| AEC-Q200    | No                                                      |
| Notes       | Number of chips in this stack: 10.                      |

#### Dimensions

|   |                   |
|---|-------------------|
| D | 26.9mm MAX        |
| L | 6.35mm MIN        |
| H | 2.54mm +/-0.127mm |
| F | 1.397mm +/-0.25mm |
| A | 6.6mm MAX         |
| B | 8.64mm MAX        |
| C | 6.35mm +/-0.635mm |
| E | 7.62mm MAX        |
| K | 0.5mm +/-0.05mm   |

#### Packaging Specifications

|                    |             |
|--------------------|-------------|
| Packaging          | Waffle, Box |
| Packaging Quantity | 25          |

#### Specifications

|                                 |                     |
|---------------------------------|---------------------|
| Capacitance                     | 0.047 uF            |
| Tolerance                       | 10%                 |
| Voltage DC                      | 2000 VDC            |
| Dielectric Withstanding Voltage | 2,400 VDC           |
| Temperature Range               | -55/+200°C          |
| Temp. Coefficient               | COG                 |
| Dissipation Factor              | 0.1% 1 kHz 25C      |
| Aging Rate                      | 0% Loss/Decade Hour |
| Insulation Resistance           | 21.28 GOhms         |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.