



Click [here](#) for the 3D model.

General Information

Series	KPS LDD Comm SMPS
Style	Leaded Stacked Chip
Description	Low ESR, High Current Stacked Ceramic Chips
Features	Low ESR, High Current, High Performance
RoHS	No
Prop 65	WARNING: Cancer and reproductive harm - https://www.p65warnings.ca.gov/
SCIP Number	4221181d-d71c-4d0a-af45-5eab760732b2
Termination	60/40 Solder Coated
Lead	L Leads
Failure Rate	N/A
Testing and Reliability	Commercial
AEC-Q200	No
Notes	Note: Number of chips in stack depends on design. Number of Chips in this stack = 3. Note: Turn Radius For Lead Extension Is 0.1 Radians (Typical). Note: Lead alignment within pin rows shall be within ± 0.13 mm.

Dimensions

D	9.845mm +/-0.955mm
L	1.78mm +/-0.25mm
T	1.397mm MAX
S	2.54mm TYP
F	0.254mm +/-0.051mm
A	9.144mm MAX
C	10.16mm +/-0.635mm
E	11.18mm +/-0.25mm
LO	1.586mm MAX
LW	0.508mm +/-0.051mm
MP	1.27mm MIN

Packaging Specifications

Packaging	Waffle, Box
Packaging Quantity	36

Specifications

Capacitance	1.2 uF
Tolerance	10%
Voltage DC	630 VDC
Dielectric Withstanding Voltage	945 VDC
Temperature Range	-55/+125°C
Temp. Coefficient	X7R
Dissipation Factor	2.5% 1 kHz 25C
Aging Rate	3% Loss/Decade Hour
Insulation Resistance	83.3 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.