


LDECC1180MA5N00

Aliases (DECC1180MA5N00)

Obsolete

LDE, Film, Metallized PEN Stacked, Automotive Grade, 1,800 pF, 20%, 50 VDC, 40 VAC, 125°C, 1812, 1.7 mm



| General Information | |
|---------------------|------------------------|
| Series | LDE |
| Dielectric | Metallized PEN Stacked |
| Style | SMD Chip |
| Features | Automotive Grade |
| RoHS | Yes |
| Qualifications | AEC-Q200 |
| AEC-Q200 | Yes |
| Shelf Life | 104 Weeks |
| MSL | 3 |

Click here for the 3D model.

| Dimensions | |
|--------------------------|-------------------|
| Chip Size | 1812 |
| L | 4.7mm +0.3/-0.2mm |
| W | 3.3mm +/-0.3mm |
| Т | 1.7mm MAX |
| В | 0.4mm +0.5/-0.3mm |
| | |
| Packaging Specifications | |
| Packaging | T&R |

Packaging Quantity

4000

| Specifications | |
|-----------------------|------------|
| Specifications | |
| Capacitance | 1,800 pF |
| Tolerance | 20% |
| Voltage DC | 50 VDC |
| Voltage AC | 40 VAC |
| Temperature Range | -55/+125°C |
| Rated Temperature | 125°C |
| Dissipation Factor | 0.8% 1kHz |
| Insulation Resistance | 1 GOhms |
| Max dV/dt | 100 V/us |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 07/09/2025 © 2006 - 2025 YAGEO