

RSBIC1680AA00K

Aliases (SBIC1680AA00K)


General Information

Series Dielectric

RSB, Film, Metallized Polyester Stacked, Automotive Grade, 6,800 pF, 10%, 250 VDC, 85°C, 5 mm

RSB

Metallized Polyester Stacked



Click here for the 3D model.	Style	Radial
	Features	Automotive Grade, DC Multipurpose Applications
	RoHS	Yes
	Termination	Cut (Tinned Wire)
	Lead	Cut
	Qualifications	AEC-Q200
	AEC-Q200	Yes
	Typical Component Weight	0.23 g
	Miscellaneous	Above 85C DC And AC Voltage Derating Is 1.25%/C.
Dimensions	Specifications	

Dimensions	
L	7.2mm +0.2mm
Н	6.5mm +0.1mm
Т	2.5mm +0.2mm
S	5mm +/-0.4mm
LL	4mm +1.5mm
F	0.5mm +/-0.05mm

Packaging Specifications	
Packaging	Bulk
Packaging Quantity	3000

Specifications	
Capacitance	6,800 pF
Tolerance	10%
Voltage DC	250 VDC
Voltage AC	160 VAC
Temperature Range	-55/+125°C
Rated Temperature	85°C
Dissipation Factor	0.8% 1kHz, 1.2% 10kHz, 2.5% 100kHz
Insulation Resistance	30 GOhms
Max dV/dt	400 V/us
Inductance	7 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 12/15/2025 © 2006 - 2025 YAGEO