

RSBMC1470Z300K

Aliases (SBMC1470Z300K)


General Information

Series Dielectric

RSB, Film, Metallized Polyester Stacked, Automotive Grade, 4,700 pF, 10%, 400 VDC, 85°C, 5 mm

RSB

Metallized Polyester Stacked



Dimensions	Specifications	
Click here for the 3D model.	Miscellaneous	Above 85C DC And AC Voltage Derating Is 1.25%/C.
	Typical Component Weight	0.23 g
	AEC-Q200	Yes
H S F	Qualifications	AEC-Q200
	Lead	Wire Leads
	Termination	Tinned Wire
	RoHS	Yes
	Features	Automotive Grade, DC Multipurpose Applications
	Style	Radial

Dimensions	
L	7.2mm +0.2mm
Н	6.5mm +0.1mm
Т	2.5mm +0.2mm
S	5mm +/-0.4mm
LL	17mm +1/-2mm
F	0.5mm +/-0.05mm

Packaging Specifications		
Packaging	Bulk	
Packaging Quantity	4000	

Specifications	
Capacitance	4,700 pF
Tolerance	10%
Voltage DC	400 VDC
Voltage AC	200 VAC
Temperature Range	-55/+125°C
Rated Temperature	85°C
Dissipation Factor	0.8% 1kHz, 1.2% 10kHz, 2.5% 100kHz
Insulation Resistance	30 GOhms
Max dV/dt	600 V/us
Inductance	7 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 11/09/2025 © 2006 - 2025 YAGEO