


## T489D476K025ATA540

T489 Auto, Tantalum, MnO<sub>2</sub> Tantalum, Commercial Grade, 47 uF, 10%, 25 VDC, SMD, MnO<sub>2</sub>, Molded, Low Leakage, Auto, AEC-Q200, 540 mOhms, 7343, 3.1 mm, 1.3 mm



Click [here](#) for the 3D model.

### General Information

|                          |                                                             |
|--------------------------|-------------------------------------------------------------|
| Series                   | T489 Auto                                                   |
| Dielectric               | MnO <sub>2</sub> Tantalum                                   |
| Style                    | SMD Chip                                                    |
| Description              | SMD, MnO <sub>2</sub> , Molded, Low Leakage, Auto, AEC-Q200 |
| Features                 | Low Leakage, Automotive                                     |
| RoHS                     | Yes                                                         |
| Termination              | Tin                                                         |
| Qualifications           | AEC-Q200                                                    |
| AEC-Q200                 | Yes                                                         |
| Typical Component Weight | 446.844 mg                                                  |

### Specifications

|                    |                                |
|--------------------|--------------------------------|
| Capacitance        | 47 uF                          |
| Tolerance          | 10%                            |
| Voltage DC         | 25 VDC (85C), 16.75 VDC (125C) |
| Temperature Range  | -55/+125°C                     |
| Rated Temperature  | 85°C                           |
| Dissipation Factor | 6% 120Hz 25C                   |
| Failure Rate       | N/A                            |
| ESR                | 540 mOhms (100kHz 25C)         |
| Ripple Current     | 527 mA (rms, 100kHz 25C)       |
| Leakage Current    | 8.8 uA (5min 25°C)             |

### Dimensions

|   |                    |
|---|--------------------|
| L | 7.3mm +/-0.3mm     |
| W | 4.3mm +/-0.3mm     |
| H | 2.8mm +/-0.3mm     |
| T | 0.13mm REF         |
| S | 1.3mm +/-0.3mm     |
| F | 2.4mm +/-0.1mm     |
| A | 3.8mm MIN          |
| B | 0.5mm +/-0.15mm    |
| E | 3.5mm REF          |
| G | 3.5mm REF          |
| P | 0.9mm REF          |
| R | 1mm REF            |
| X | 0.1mm +/-0.1mm REF |

### Packaging Specifications

|                    |            |
|--------------------|------------|
| Packaging          | T&R, 178mm |
| Packaging Quantity | 500        |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.