


## T493X157K010CH642C

T493 Space, Tantalum, MnO2 Tantalum, Space, 150 uF, 10%, 10 VDC, SMD, MnO2, Molded, Aerospace, C (0.01%/1000 Hrs), 150 mOhms, 7343, 4.3 mm, 1.3 mm



| General Information      |  |
|--------------------------|--|
| Series                   | T493 Space   |
| Dielectric               | MnO2 Tantalum  |
| Style                    | SMD Chip   |
| Description              | SMD, MnO2, Molded, Aerospace   |
| Features                 | Aerospace  |
| RoHS                     | No   |
| Prop 65                  | WARNING: Cancer and reproductive harm - https://www.p65warnings.ca.gov / |
| SCIP Number              | 1dd2e1b8-26dd-4d52-927c-6f9<br>d519011aa                                 |
| Termination              | Tin Lead (SnPb)  |
| AEC-Q200                 | No   |
| Typical Component Weight | 654.04 mg  |

| Dimensions |                    |
|------------|--------------------|
| L          | 7.3mm +/-0.3mm     |
| W          | 4.3mm +/-0.3mm     |
| Н          | 4mm +/-0.3mm       |
| Т          | 0.13mm REF         |
| S          | 1.3mm +/-0.3mm     |
| F          | 2.4mm +/-0.1mm     |
| A          | 3.8mm MIN          |
| В          | 0.5mm +/-0.15mm    |
| E          | 3.5mm REF          |
| G          | 3.5mm REF          |
| P          | 1.7mm REF          |
| R          | 1mm REF            |
| X          | 0.1mm +/-0.1mm REF |

| Specifications          |  |
|-------------------------|--|
| Capacitance             | 150 uF   |
| Tolerance               | 10%  |
| Voltage DC              | 10 VDC (85C), 6.7 VDC (125C)   |
| Temperature Range       | -55/+125°C   |
| Rated Temperature       | 85°C   |
| Dissipation Factor      | 8% 120Hz 25C   |
| Failure Rate            | C (0.01%/1000 Hrs)   |
| ESR                     | 0.15 Ohms (100kHz 25C)   |
| Ripple Current          | 1049 mA (rms, 100kHz 25C)  |
| Leakage Current         | 15 uA (5min 25°C)  |
| Testing and Reliability | 10 Cycles Surge Testing At -55C<br>And +85C Before Weibull;<br>Additional Testing Option C |

| Packaging Specifications |            |
|--------------------------|------------|
| Packaging                | T&R, 178mm |
| Packaging Quantity       | 500        |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 11/01/2025 © 2006 - 2025 YAGEO