


CATHODE (-) END VIEW

T556B396K060AT

T556, Tantalum, Polymer Tantalum, HRA, 39 uF, 10%, 60 VDC, N/A, 160 mOhms, 9.6 mm, 3 mm

BOTTOM VIEW



General Information T556 Series Dielectric Polymer Tantalum Style SMD Chip RoHS No SCIP Number 43449f08-bd3e-4b72-a04c-6c a7dd4144ff Termination Tin AEC-Q200 No Typical Component Weight 5.54 g Shelf Life 156 Weeks

Click here for the 3D mo	del.

► S -

- S

SIDE VIEW

Dimensions	ensions	
L	24.5mm +/-0.5mm	
W	8.5mm +/-0.5mm	
н	9.1mm +/-0.5mm	
S	3mm MIN	
F	4.2mm +/-0.5mm	

Packaging Specifications		
Packaging	Bulk, Box	
Packaging Quantity	100	

Specifications	
Capacitance	39 uF
Tolerance	10%
Voltage DC	60 VDC, 46.8 VDC (105°C), 39.6 VDC (125°C)
Temperature Range	-55/+125°C
Life	2000 Hrs
Dissipation Factor	5% (120Hz 25C)
Failure Rate	N/A
ESR	160 mOhm (100kHz 25C)
Ripple Current	1310 mAmps (40kHz 85C)
Leakage Current	17.6 uA (5min 25°C)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute – and we specifically disclaim – any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.